mont-bell 共通取扱説明書

キャンプパッド シリーズ

Camp Pad Series

この度はお買いあげいただき、誠にありがとうございます。この取扱説明書(以下「本説明書」といいます) は本製品の正しい取扱方法を説明しています。ご使用の前に本説明書をよくお読みいただき、正しい使用 方法をご確認ください。なお、ご不明な点等ございましたら、販売店もしくは(株) モンベル カスタマー・ サービスまでお問い合わせください。本説明書は大切に保管してください。

■ 特長

本製品は、地面からの冷えや突き上げを緩和し、快眠をサポートするフォーム入りスリーピングパッドです。 独自のU.L.コンフォートシステムにより、本製品に枕を固定させたり長さの異なるパッドなどを連結できます。 寝返りで枕がずれたり、すき間を作ることがないため、快眠を妨げません。また、収納袋がポンプバッグとし て使用でき、簡単に空気を入れることができます。





1

■ 安全上の注意 「必ずお読みください

登客告 場合により人が死亡または重傷を負う可能性が想定される内容です。 軽傷または物的損害が発生する頻度が高いことが想定される内容です。

○本製品を絶対に浮き袋の代わりに使用しないでください。

注意 人が傷害を負ったり物的損害の発生が想定される内容です。

- ○正しいお手入れ方法、保管方法を守ってください。誤ったお手入れや保管方法を行うと、本来の性能を 発揮できない恐れがあります。
- ○本製品の改造や分解などは絶対にしないでください。性能が損なわれ、十分に機能が発揮できない恐れ があります。
- ○本製品を使用する際は、表地に直接頭部や肌があたらないようにタオルなどをかぶせて使用することをお 勧めします。整髪料や頭部の皮脂などが本製品に染み込み、牛地の剥離を促進する恐れがあります。
- ○高圧ポンプやコンプレッサーを絶対に使用しないでください。破損の恐れがあります。
- ○使用前は毎回必ず点検をしてください。老朽化が認められる場合や損傷が認められたり、疑わしい場合 は直ちに本製品の使用を中止してください。本来の性能が発揮できない恐れがあります。
- ○本製品の設置場所にトゲのある茂みや尖った石などがないかを常に確認してください。パンクの原因とな ります。
- ○本製品を地面に直に置いて使用しないでください。テントの中で使用するなど、保護のために本製品の 下にグラウンドシートなどを敷いてください。
- ○空気を限界まで封入した状態で急激な圧力を加えないでください。内部のフォームが破損する恐れがあり ます。
- ○本製品を火気や熱いものに近づけないでください。本体、フラットバルブの変形や損傷の原因となりま す。また、使用直後の火器(コンロ、ランタンなど)が本製品に触れないよう十分にご注意ください。
- ○本製品をご使用中の喫煙はお避けください。落下した灰が生地を傷める恐れがあります。
- ○気温の高い日に膨らませてフラットバルブを閉めた本製品を車内やテント内に放置することはお避けくださ い。パンクの原因となります。
- ○日焼け止め、塩素を含む薬品などが本製品に付着しないようにしてください。生地とフォームが剥離す る恐れがあります。
- ○本製品を長期間直射日光に晒さないでください。紫外線劣化により本製品の耐久性が損なわれる恐れが あります。
- ○本製品はペットが触れることのできない場所に置いてください。ペットが噛みついたり、本製品に爪が引っ 掛かったりすることで穴が開く恐れがあります。
- ○使用時は身につけている金具に注意してください。就寝中にズボンのバックルなどが生地を傷める恐れ があります。
- ○本製品を収納する際は、十分乾かしてから収納してください。生地の劣化やカビの原因になります。

■ 使用前の点検

使用にあたっては、毎回必ず次のことを確かめてください。 異堂が見られた場合は使用しないでください。

	71111 2021412			
□穴が開いていないか		□生地カ	剥	雛して
□フラットバルブが破損して	いないか	□空気カ	~漏;	nt

ていないか いないか

■ 使用方法 ※イラストはキャンプパッド 38 150で説明しています。

○ 初めてご使用になる前に

本製品はフォームの復元力を利用して半自動的に吸気する機能があります。ただし、空気が抜かれた状態で出 荷されているため、初めてご使用になる前に本製品を膨らませて、空気を入れた状態で一晩置き、フォームの クッション性と復元力を回復させてください。(※後述の空気の入れ方をご覧ください。)

また、本製品の空気を抜いた状態で長期間収納袋に入れて保管した場合も上記のように、ご使用前にクッショ ン性と復元力を回復させてください。

空気の入れ方

本製品は、2通りの膨らませ方ができます。

○半自動的に膨らませてから、ポンプバッグ(収納袋)を使用して、空気を入れる方法。(1、2をご覧ください。) ○初めからポンプバッグ(収納袋)を使用して空気を入れる方法。(図をご覧ください。)

日半自動的に空気を入れる方法

●本製品を収納袋から取り出します。 2フラットバルブのキャップを開きます。 ③キャップのタブを内側の弁に差し入れます。フラットバルブにすき 間ができることで、フォームが自動的に吸気します。 ※本製品を完全に膨らませることはできません。

⑤空気を入れ終わったら、キャッ

プをフラットバルブにしっかり

押し込み、フラットバルブを閉



❹吸気が止まったら、差し込んでいたキャップのタブを抜き、内側の弁が閉じ ていることを確認してください。さらに膨らませる場合は、ポンプバッグ(収 納袋)を使用して空気を送り込みます。(後述2-2をご覧ください。)



2 ポンプバッグ(収納袋)を使用する場合

 本製品を収納袋から取り出します。 本製品とポンプバッグ(収納袋)のフラットバルブのキャップを開き、接続します。 ※弁が開いている場合は、 一●を参照してください。 	③ポンプバッグ(収納袋) に空気を溜め、開口部 を握り空気が漏れない ようにしっかり閉じます。	 ポンプバッグに体重をかけ、ポンプバッグ内の空気を本製品へ入れます。 金を数回繰り返してください。 その際、バルブの真上を避けてポンプバッグを押してください。 	 空気を入れ終わった ら、キャップをフラット バルブにしっかり押 し込み、フラットバル ブを閉じます。
・ ・ キャップ フラット バルブ			押し込む

○気温が低い時は本製品の膨らみが遅くなることがあります。その際は、広げた本製品の上にしばらく横に なるなどしてフォームを温めると膨らみやすくなります。

⚠注意

○空気を限界まで封入した状態で急激な圧力を加えないでください。内部のフォームが破損する恐れがあ ります。

○ ピローストラップ(特許取得済)

スリーピングバッグの収納 ピローストラップ 袋などを枕として使用する 際に、本製品に固定するス トラップです。枕がずれない ことで朝まで快眠できます。

○ ジョイントシステム(特許取得済)

トグルと穴を利用して二つのパッドを 連結することができます。パッド以外 にもししコンフォートシステムピロー (別売)やエクステンションパッド30 (別売)の連結ができます。寝返りを 打ってもパッドがずれず、快眠を妨げ ません。



穴にトグルを通します

- ●フラットバルブのキャップを開け、キャップのタブを内側の弁に差し込みます。 (半自動的に吸気させる場合の⑥をご覧ください。)本製品を軽くたたみ、体重 をかけて空気を押し出します。
- ②空気がある程度抜けたら、フラットバルブのキャップを一旦閉じます。montbellのロゴマークが地面側になるように本製品を置き、上下のトグルをそれぞ れつなぎ縦に折り曲げます。(イラスト1)

※キャンプパッド38 180、キャンプパッド50 150/180は折り曲げず、そのまま 日に進みます。

③フラットバルブの反対側の端から強く押さえながらゆっくりと本製品を巻きます。 ある程度まで巻いたら、再びフラットバルブのキャップのタブを内側の弁に差し込 み、残りの空気を出し切ってください。(イラスト2)

④巻き終わったあとは空気が入り込まないように素早くフラットバルブのキャップ を閉じ、最後にピローストラップで固定します。(イラスト3)



ピローストラップ

⑤収納袋へ収納します。持ち運びの際は収納袋に入れ、パッド本体の生地に 穴が開かないよう保護してください。

修理方法

本製品に穴(ピンホール)が開いた場合

付属の補修キットで補修することができます。

- ※大きな穴が開くなどした場合は、お買い求め頂いた販売店、もしくは下記の弊社カスタマーサービスへご 連絡ください。
- ●十分に本製品を膨らませて、空気の漏れている穴の位置を確認します。分かりにくい場合は水に浸すか 石鹸水を疑わしい部分に塗って加圧してください。小さな気泡の発生する場所が穴の位置です。穴に印を 付けてできるだけ本製品の空気を抜きます。
- ❷石鹸水を塗った場合は水で良く洗い流し、完全に乾燥させてください。濡れていたり石鹸水がついたままでは パッチが本製品に接着しません。
- ❸本製品に開いた穴から外側に向かって同心円状に接着剤をうすく伸ばして塗り、5分間ほど乾かします。そ の際、必ず付属のパッチより少し大きい範囲で接着剤を塗ってください。
- ④パッチの裏の紙をはがして接着剤を塗った箇所に貼り合わせます。表面が平らで硬いもので暫くパッチを押 さえ、浮いている箇所がないことを確認してください。

4

⑤接着剤が完全に乾くまで空気を抜いた状態で放置します(約8時間程度)。

⑥パッドを膨らませ、空気の漏れがないことを確認します。



イラスト1

弁の交換方法

弁が傷んで空気漏れ等の不具合が生じた際は、補修キットの弁と交換してください。万一、弁が外れた場合は❸ からの手順で取り付けてください。パーツが小さいため、必要に応じてピンセットなどをご使用ください。



❷持ち上がったBを持ち、Dの穴から引き抜き、古い 弁を取り外します。



④Aを持ち、しっかりDの穴から引き出します。その 際、Cの膨らんだ部分を穴から完全に出してくださ い。完全に出さないと、弁が本製品の内側へ脱落 する恐れがあります。







●Aを3mm程度残すようにカットします。Cの部分

することで、キャップとの干渉を防ぎます。

までカットしないよう注意してください。Aをカット

❸Dを指で持ち上げ、Dの穴に新しい弁のAを下

から诵します。

- お手入れ方法
- 間違ったお手入れ方法や保管方法は本製品の寿命を縮めます。 使用後や保管時は以下の点を参考にしてください。

○汗や皮脂などの汚れが付いた際は、ご使用後すぐに中性洗剤で洗ってください。 汚れを放置すると、それらが染み込むことで生地が剥離して空気漏れの原因になります。

○本製品を最大限に膨らませた状態でフラットバルブをしっかりと閉じます。毛の柔らかいブラシと、家庭用の中性 洗剤を用意し、ぬるま湯(30℃以下)で洗ってください。洗浄後は十分にすすぎ、完全に乾燥させてください。

■ 保管方法

- ○風通しがよく、湿度が高くならない場所で、直射日光を避けて保管してください。
- ※本製品の経年劣化を早める恐れがあります。以下のような場所に保管しないでください。
 - ・直射日光のあたる庭の物置 ・車内や車のトランクなど高温になる場所
- ○長期間保管する場合は、パッドを広げ、フラットバルブを開いたまま湿気のない場所で保管してください。普 段から本製品を広げておくことでパッドのフォームが膨らみ、復元力が高まります。
- ○本製品を濡れたまま長期間放置しないでください。生地を傷める恐れがあります。
- ○保管時は刃物や鋭利な物と接触させないでください。



○廃棄方法はお住まいの自治体の収集方法に従ってください。

■ アフターサービス

お買い求めいただきました本製品は万全を期して製造しておりますが、万一不備な点がございましたら、お買 い求めいただいた販売店、もしくは下記の弊社窓口までご連絡ください。

製造上の欠陥による不具合の場合は無償で交換させていただきます。なお、修理、交換等の要否につきまし ては、弊社の裁量にて判断させていただきます。

なお、以下のような原因での破損、不良につきましては保証いたしませんのでご了承ください。

○本製品の誤った使用方法によるもの ○間違ったお手入れ、保管方法、経年変化による素材劣化 ○乱暴な取り扱いによるもの ○その他、製造上の欠陥以外の原因によるもの 破損時は弊社にて診断をして、修理が可能な場合はご要望により有償にて修理をさせていただきます。

■ ジョイントシステム対応モデル

● U.L. コンフォートシステム エアパッド ワイド/キャンプパッド38.50 ※エアパッドワイド・キャンプパッドで、長さが同じパッド同十を連結できます。 ※キャンプパッド100は連結に対応していません。

● U.L. コンフォートシステム ピロー

エクステンションパッド30



麦 材: 30 デニール・ポリエステル・リップストップ [TPU ラミネート]、ウレタンフォーム

■ その他

本製品の仕様、デザインは予告なく変更されることがあります。また、重量などのスペックには誤差が生じる場合があります。

##ご会社 デンベル 本社 〒550-0013 大阪市西区新町2-2-2 https://www.montbell.ip/ 商品についてのお問い合わせはカスタマー・サービスまで Tel.06-6531-3544 フリーコール:0088-22-0031 6

44-5133-2208

mont-bell User's Manual

Camp Pad Series

Camp Pad Series

Thank you for purchasing this product. Before using, please carefully read this manual for instructions on the proper care and usage of this product.

If you have any questions regarding this product, please contact Montbell Customer Service or the store of original purchase. Keep this manual for future reference.

Features

Provides insulation from the ground and cushions against protrusions for a good nights rest. Based on our original design, the U.L. Comfort System can be used to connect pads of varying lengths or hold a pillow in place. The system prevents the pad and pillow from shifting during sleep and creating spaces that can cause waking. Use included stuff sack as a pump bag to inflate.





Safety Warnings! Please read carefully.

WARNING! Under certain conditions, use of this product can result in injury, death, or property damage.

 \bigcirc Do NOT use as a flotation device.

CAUTION: Under certain conditions, use of this product can result in injury or property damage.

- ○Please follow recommended care and storage instructions. Improper care and storage can lead to a decrease in performance.
- ODo NOT modify or alter this product. Improper modifications and alterations can damage the product and impair function.
- ○Do NOT allow pad to come into direct contact with the head or skin. Hair oils and the skin's natural oils can soak into the material and cause it to prematurely break down. Use a barrier to prevent direct contact, such as a towel or sleeping bag.
- ODo NOT inflate with an air compressor.
- ○Prior to use, check the pad's condition and stop using immediately if you notice any deterioration from age/use, damage or irregularities.
- \bigcirc It is important to use caution when around sharp objects (thorns, branches, stones, cacti, etc), that may puncture the material.
- \bigcirc When not sleeping in a tent, use a ground cloth to protect the pad.
- \bigcirc Do NOT apply sudden pressure to pad when fully inflated. May cause the pad to rupture.
- OKeep this product away from flame sources, such as campfires, to prevent damage and warping due to heat. Do NOT set hot objects (such as a hot stove or lantern) on top of the pad.
- \bigcirc Do NOT smoke over the pad. Hot ash can damage the fabric.
- \bigcirc Do NOT leave inflated pad inside a tent or car during hot weather. May cause the pad to rupture.
- ○Do NOT expose to chlorine based chemicals and sun screen. Can cause the material to break down prematurely.
- OAvoid long-term exposure to sunlight. Ultraviolet light can damage the material.
- \bigcirc Store out of the reach of pets. Pets can bite or claw the material, causing holes.
- ⊖Avoid wearing metal objects when using, such as a pair of pants with buckles. May damage the pad while sleeping.
- Ory this product thoroughly before storing. If stored while wet, mold may form and the fabric may deteriorate prematurely.

Prior to use, inspect this product for: Stop using immediately if you notice any irregularities.

Punctures
Damage to the valve

□Fabric peeling
□Air leakage

Directions *Illustration shows Camp Pad 38 150.

 \bigcirc Before Using the pad

Although this pad's foam has a small degree of self-inflating abilities, it is shipped in a completely compressed state. Before using for the first time, open the valve and wait for the pad to self-inflate before using the Pump Bag to inflate to capacity. Leave the inflated pad to rest over night to allow the foam to recover its cushioning and self-inflating abilities.

After storing the pad for an extended period of time, follow the same procedure above for restoring the foam.

\bigcirc Inflating the pad

Inflate in two ways.

OAllow pad to semi-automatically inflates partway, then fully inflate with pump bag (stuff sack). (Refer to 1 and 2.)

 \bigcirc Use pump bag (stuff sack) to inflate. (Refer to **2**.)

1 Self-inflating

Remove from stuff sack (pump bag). **2**Open the valve cap.

Insert the cap's tab into the valve to create a gap in the seal. By opening the valve, air is able to flow into the pad. *Will NOT fully self-inflate.







After the pad has time to self-inflate, remove the cap's tab from the valve. Make sure the seal is closed. If the pad needs more air, inflate with pump bag (Refer to 2-2)

GPush in cap firmly to secure.



2 Inflating with the pump bag

1 Remove from stuff sack **3** Open the bag and roll **4** Place your weight on **5** Push in cap firmly (pump bag). **2**Attach the pump bag to the pad's valve. *If seal is open, use a finger to push the seal into the pad. (cf.Inflating 1-4)





the opening down so

that it captures air

inside the bag.



the pump bag so air

moves into the pad.

personal preference.

until inflated to

Repeat steps 3 and 4



to secure.

- A Caution! Oln cold weather, the pad can take longer to self-inflate. Spread out the pad and lay on it to warm the foam, which helps the foam expand.
- ODo NOT apply sudden pressure to pad when fully inflated. May damage the pad's foam.

O Pillow Strap (patented)

Once the pad is unrolled. the strap and buckle can be used to secure a pillow in place. This way the pillow does not require repositioning throughout the night and allows for uninterrupted sleep.



It is possible to connect 2 sleeping pads together by the toggles located on the sides of the pads. Additional accessories are also attachable via these points.

○ Joint System (Patented)



Loop a toggle through the evelet

• Deflating the pad

Open the cap and insert the cap's tab into the valve (See Self-inflating Step 2). Fold the pad and use your weight to push air out of the pad.

2 Lay the pad on the ground so the Montbell logo faces the ground and close the valve. Connect the toggles and evelets together (See Fig. 1). (For the Camp Pad 38 150 or Camp Pad 50 150 / 180, folding is not required)



Pillow strap

GFirmly roll up the side opposite the valve. After rolling up the pad, once again open the valve and push out remaining air. (See Fig. 2)

After deflating the pad completely, close the valve and secure the pad with the pillow strap. (See Fig. 3)

5Put the pad into its stuff sack. Take caution not to puncture the pad during transport.

🔿 Repair

Punctures (pin hole sized)

If the pad becomes punctured (pin hole sized), use the included repair kit to patch the hole. For larger holes, contact the original store of purchase or Montbell Customer Service.

- First locate the puncture. If you cannot find the hole, inflate the pad and then coat any suspicious areas with soapy water. Pressure from the inside should cause the soapy water to bubble, showing you the location of the puncture.
- **2**If using the procedure in step **1**, make sure the pad is thoroughly rinsed, completely dry and deflated before continuing.
- 3 Apply the adhesive to the puncture and the area around it. Make sure the area covered by the adhesive is larger than the patch. (It is possible to cut the included patches to a desired shape. Make sure to avoid rectangular shapes; the corners have a tendency to peel)

OPeel the backing off of the patch and firmly press the patch directly onto the puncture. Hold patch in place for a few minutes.

6Let dry for at least 8 hours.

6 Check to see if your repair was successful, or if there are more punctures.

3

Use the method below to replace the seal if it becomes damaged or detached.

Since parts are small, if necessary use tweezers.



2Pull the seal out of the seat.



4Firmly hold the seal's stem and pull through the hole in the seat. Make sure the bulb on the stem (C) completely passes through the hole in the seat. This bulb prevents the seal from becoming loose and falling into the pad.







Care

Improper care and storage can shorten the lifespan of this product. Follow the recommendations below to extend the lifespan of your product.

Olf perspiration or the skin's natural oils come into contact with the product, wash with a mild soap. Contact can cause the material to break down prematurely.

OInflate the pad to its maximum capacity and close the valve's cap. Wash using a soft brush, mild soap and lukewarm water (below 30°C). Rinse thoroughly and allow to air dry before storing.

Storage

- Ostore in a well ventilated, cool, dry place out of direct sunlight.
- The following storage methods can cause this product to deteriorate guickly.
- -Any area that receives exposure from direct sunlight.
- -A car trunk or other area subject to high temperatures.
- OFor long term storage, store in a dry place with the pad spread out with the valve open. Storing the pad spread out aids the foam's cushioning and self-inflating abilities.
- ODo NOT store this product while wet. Molding and premature fabric deterioration can occur if stored while wet. Drv thoroughly before storing.
- ODo NOT allow sharp or pointed objects to come into contact with the pad.

OPull the seal's stem (A) out of the valve and hold the seal (B).



3Hold up the seat and pass the new seal's stem (A) through the hole in the seat.



5Cut the seal stem (A) while leaving about 3mm remaining. This prevents interference with the cap. Do NOT cut down to the bulb (C).

Disposal

OPlease follow local regulations regarding waste disposal.

Warranty

Montbell's warranty covers all defects in materials and workmanship to the original owner, for the lifetime of the product. If a product ever fails due to a manufacturing defect, Montbell will repair or replace the product at Montbell's discretion. This warranty does not cover damage(s) caused by accident, improper care, negligence, misuse, alterations or normal wear and tear. Damage(s) not covered under warranty will be repaired at a reasonable rate. If you would like to make a warranty inquiry, please contact Montbell Customer Service or the store of original purchase.

Joint System compatible

- U.L. Comfort System Air Pad Wide / Camp Pad 38, 50 *Can connect Air Pads Wide with Camp Pads. Applies ONLY to pads with the same lengths. *NOT compatible with Camp Pad 100.
- U.L. Comfort System Pillow
- Extension Pad 30

Specifications

Materials: 30-denier polyester rip-stop [TPU laminate], Urethane foam

All product specifications and design are subject to change without prior notice. Actual product specifications may vary.

